




One-Stop Service For APG Process Producing For Electrical Insulators Vacuum Mixing Injection Device

Our Product Introduction

for more products please visit us on jc-transformer.com

Basic Information

- Place of Origin: China
- Brand Name: JC
- Certification: SGS CE,UL
- Model Number: YU9088



Product Specification

- Clamp Force: 22t
- Transport Package: Wooden
- Production Capacity: 60000PCS/Year
- Clamp Plate Size: 1000X1000MM
- Min Max Clamp Plate Stroke: 250X1650mm
- Upper & lower Core Puller Stroke: 900X400mm
- Application: Mixing And Injection
- Injection Accuracy: $\leq \pm 1\%$
- Injection Pressure: 0-0.4MPa
- Material: Stainless Steel
- Mixing Accuracy: $\leq \pm 1\%$
- Mixing Capacity: 2-50L
- Mixing Speed: 0-3000rpm
- Mixing Tank: 50L



More Images



Product Description

One-Stop Service for APG Process Producing for Electrical Insulators

· Application-Standard APG clamping machine:

This series belongs to Standard APG clamping machine, the min clamp plate size is 600X800mm, and the Max clamp plate size is: 1200X1000mm, can meet production requirement from 11-36KV, such as current transformer, voltage transformer, insulator, bushing, spout, SFG gas-insulated indoor switch disconnector. Etc.

The upper and lower core distance can be customized, foundation pit is necessary if lower core travel distance above 500mm.

· Main Machine Technical Parameters:

| 型号 Model No. | HAPG-860 | HAPG-880 | HAPG-1000 | HAPG-1210 |
|---|--------------|---------------|---------------|---------------|
| 模板尺寸 clamp plate size | 600X800mm | 800X800mm | 1000X1000mm | 1200X1000mm |
| 合模力 clamp force | 18T | 18T | 21T | 21T |
| 最小最大合模距离 Min/Max clamp plate stroke | 240X1250mm | 240X1250mm | 240X1450mm | 240X1450mm |
| 上下抽芯行程Upper&lower core puller stroke | 760X350mm | 760X350mm | 760X450mm | 760X450mm |
| 加热功率 Heating power | 12KW | 16KW | 24KW | 24KW |
| 液压站功率 hydraulic station power | 5.5KW | 5.5KW | 5.5KW | 5.5KW |
| 倾斜角度 Horizontal tilting angle | 0-5° | 0-5° | 0-5° | 0-5° |
| 装模重量 mould load weight | 2T | 2T | 3T | 3T |
| 整机重量 Machine weight | 4500KG | 4800KG | 5300KG | 5700KG |
| 整体尺寸 Machine dimension | 3.1X1.3X2.5m | 3.1X 1.3X2.5m | 3.4X1.15X2.8m | 3.4X1.15X2.8m |

Product Description

APG Machine = Automatic pressure gel equipment

APG machine with Epoxy Resin for Electric Insulation of 38KV Outdoor Transformer CT and PT.

It has been nineteen years and has been developing into DMC after continuous development. S hydraulic press, epoxy resin pressure gel forming machine, full automatic Epoxy Static system and metal extrusion hydraulic press and other equipment, and can design and manufacture various kinds of special equipment according to the needs of high-voltage electrical appliances users.

Servo HAPG Clamping Machine

This machine is full automatic, Servo and Pic touch screen control Machine, the clamp plate size n customized, greatly improved efficiency and product quality Advantages

1. Servo motor control
2. PLC touch screen control
3. Can save more than 100 product datas
4. Fully automatic design

Auto start machine heating clamp plate Auto setting hydraulic pressure Auto setting heating temperature Auto setting valve flow



APG FACTORY



· APG Claming Machine Production Process:



APG MACHINE SAFETY SHIPPING




**Offer debugging and APG
technique training overseas**

Products made by APG Machine:

Products made by APG machine:

10~35KV Current Transformer

10-35KV 电流互感器



10~35KV Potential Transformer

10-35KV 电压互感器



Insulator Series

绝缘件



Wuxi Jiachen Power Electronics Equipment Co., Ltd.



tangliang@jc-cores.com



jc-transformer.com

No. 68, Zhounan Road, Wanshi Town, Yixing City, Jiangsu Province, China