



Cold Rolled Grain Oriented Electrical Steel Grade 35g145 For Large Motor

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: JC
- Certification: SGS CE,UL
- Model Number: 35G145
- Minimum Order Quantity: 1
- Price: consult
- Packaging Details: Standard export package for ocean transportation
- Delivery Time: 5 days
- Payment Terms: L/C, T/T, Western Union, MoneyGram
- Supply Ability: 200Ton/week



Product Specification

- Trademark: Baosteel; WISCO; Nippon Steel; JFE; AK
- Coating: Electro Galvanized, Hot Dip Galvanized
- Coating Color: RAL Color
- Impact Test: No Crack
- Length: 1000mm-2000mm
- Material: CRGO&CRNGO
- Surface: Smooth
- Thickness: 0.23mm-0.35mm
- Grade: M1, M2, M3, M4
- Package: Standard Export Packing
- Width: 1000mm-1250mm
- Type: Oriented Silicon Steel
- Standard: GB, AISI, ASTM, DIN, JIS
- Technique: Cold Rolled
- Shape: Coil



More Images



Product Description

Oriented Electrical Steel Grade 35g145 Used for Large Motor

Basic Info.

Model NO.	35G145
Trademark	Baosteel
Origin	China
HS Code	72251100
Production Capacity	5000mt/Month

Product Description

Ordering Instruction(for prime coils or slit coils):

1, Which Grade? if you do

not know the exact grade, please tell us below:

1), What's the thickness of the material?

2), What's the core losses @1.7T/50Hz(or 60Hz), for Non-Oriented electrical steel, please tell the core losses@ 1.5T/50Hz or 60Hz;

2, What's the desination or discharge port?

3, How about the quantity?

If any technical issue about the prime coils or related to cores, welcome to contact us anytime.

Detailed description as below:

Major Manufacturer	BAOSTEEL, WISCO, Nippon Steel, JFE, AK
Grade	CRGO: 20ZDKH75, B20P075, B20P070, B18R070 B23G110, B23G100, B23P100, B23R095, B23R090, 23ZH90,23QG090, B23R080 27Q120, 27QG100, 27QG095, B27P120, B27P100, B27P095 30Q130, 30Q120, 30QG105; B30G130, B30G120, B30P120, B30P105 35Q155, B35G155, 35Z155 CRNGO: B35A270, B35A250, B35A230, B35A300, 35WW270,35WW250,35WW230 B50A800, B50A600, B50A470, B50A400, B50A310, B50A290, B50A250, B50A1300, B50A1000
Nominal thickness	0.18mm, 0.20mm, 0.23mm,0.27mm,0.30mm,0.35mm, 0.5mm
Coil ID	508mm
Weight	2MT~8MT
Standard	EN 10106,IEC 60404-8-4,ASTM,DIN,GB,JIS
Form	Cold Rolled Strip
Delivery Lead Time	7~15 days after T/T prepayment or L/C date
Packing	Standard export package for ocean transportation
Application	All kinds of transformer, reactor,filter,inverter

Specification of CRGO silicon steel products

Type	Grade	Thickness (mm)	Available width range (mm)	ID	Density (kg/dm ³)	P _{17/50} Max.Core Loss(W/kg)	B ₈ Min. Induction(T)
	B23G110	0.23				1.10	1.80

High Induction Type	B27P100	0.27	700-1200	508	7.65	1.00	1.88
	B27P110					1.10	1.88
	B30P100					1.00	1.88
	B30P105					1.05	1.88
	B30P110	0.30				1.10	1.88
	B30P120					1.20	1.88
	B35P135					1.35	1.88
	B35P155	0.35				1.55	1.88
Domain Refined High Induction Type	B23R080					0.80	1.87
	B23R085	0.23				0.85	1.87
	B23R090					0.90	1.87

B 2 7 R 0 9 0	0.27				0.90	1.87
B 2 7 R 0 9 5					0.95	1.87

NOTE:

Detecting Basis GB/T3655-2000

P17/50 means core loss of sample per kg at max.magnetic induction 1.7T and frequency 50HZ

B8 means magnetic induction corresponding to 800A/m magnetic field intensity

Oriented Electrical Steel Grade 35g145 Used for Large Motor
Oriented Electrical Steel Grade 35g145 Used for Large Motor
Oriented Electrical Steel Grade 35g145 Used for Large Motor
Oriented Electrical Steel Grade 35g145 Used for Large Motor
Oriented Electrical Steel Grade 35g145 Used for Large Motor
Oriented Electrical Steel Grade 35g145 Used for Large Motor



Wuxi Jiachen Power Electronics Equipment Co., Ltd.



tangliang@jc-cores.com



jc-transformer.com

No. 68, Zhounan Road, Wanshi Town, Yixing City, Jiangsu Province, China