

3 Dimensional Uni-Core For S13 250kVA Distribution 3d Wound Core **Transformer**

Basic Information

China • Place of Origin: • Brand Name: JC

SGS CE,UL . Certification: • Model Number: 2500kva Minimum Order Quantity: 200kg • Price: consult

• Packaging Details: Export standard packaging

• Delivery Time: 5 days

• Payment Terms: L/C, T/T, Western Union, MoneyGram

. Supply Ability: 500mt/Month



Product Specification

• Application: Power, Electronic

• Phase: Single

• Core: Shell-type Transformer

. Cooling Method: Oil-immersed Type Transformer Winding Type: Multi-winding Transformer · Certification: ISO9001-2000, ISO9001

1.2 GHz

8 GT/s • Bus Speed:

16 MB Intel Smart Cache · Cache: Intel UHD Graphics 630 • Graphics:

• Graphics Max Dynamic Frequency:

• Graphics Video Max

Memory:

• Max Memory Size: 128 GB • Max Turbo Frequency: 5.1 GHz Maman, T. DDD4 0000

64 GB



More Images











Product Description

Customized 3 Dimensional Uni-Core for S13 250kVA Distribution Dry Type Transformer

Basic Info.

Model NO. 100KVA

Product Description

Usage	Single-phase Transformer, Rectifier Transformer, Combined Transformer, Power Transformer, Distribution Transformer	Introduction: Our Uni-cores are widely used in distribution transformers, especially for S13 type energy-saving transformers in China; we could also provide our customers with single phase wound cores like D9, D10, D11 etc., three phase Uni-cores; The capacity range from 10KVA to 25000KVA; Due to its particular technology craft, its performance is better than traditional stacked cores, especially for pole-mounted single phase transformers and 3 Dimensional transformers(3D transformers).
Frequency Characteristics	Power Frequency	
Shape of Core	Uni-Core	
Brand	Jc Cores	
Transport Package	Standard Export Package for Ocean Transportation	Manufacturing requirements:
Specification	100kVA	Tolerance: See demonstrated graphic; the specified requirements should be coincide
Origin	China	with customers drawings; Material: we could choose Nippon steel, Baosteel, WISCO and other steel plants products to meet customers core loss requirements; in order to make sure we
HS Code	8504901900	
Production Capacity	500mt/Month	

choose the right material, we would like our customers to provide us with detailed drawings including necessary technical parameters.

Detailed ordering instructions below:

- 1, All sizes in the pictures?
- 2, Frequency (50Hz or 60Hz)?
- 3, Low voltage;
- 4, Turns (@ low voltage)
- 5, Max. No-load core losses?

Uni-Core for S13 100kVA Distribution Dry Type Transformer

Introduction:

Our wound cores are widely used in distribution transformers, especially for S13 type energy-saving transformers in China; we could also provide our customers with single phase wound cores like D9, D10, D11 etc., three phase wound cores; The capacity range from 10KVA to 2500KVA; Due to its particular technology craft, its performance is better than traditional stacked cores, especially for pole-mounted single phase transformers

Manufacturing requirements:

Tolerance: See demonstrated graphic; the specified requirements should be coincide with customers drawings:

Material: we could choose Nippon steel, Baosteel, WISCO and other steel plants products to meet customers core loss requirements; in order to make sure we choose the right material, we would like our customers to provide us with detailed drawings including necessary technical parameters.

Detailed ordering instructions below:

- 1, All sizes in the pictures?
- 2, Frequency (50Hz or 60Hz)?
- 3, Low voltage;
- 4, Turns (@ low voltage)
- 5, Max. No-load core losses?

Introduction:

Our Uni-cores are widely used in distribution transformers, especially for S13 type energy-saving transformers in China; we could also provide our customers with single phase wound cores like D9, D10, D11 etc., three phase Uni-cores; The capacity range from 10KVA to 25000KVA; Due to its particular technology craft, its performance is better than traditional stacked cores, especially for pole-mounted single phase transformers and 3 Dimensional transformers).

Manufacturing requirements:

Tolerance: See demonstrated graphic; the specified requirements should be coincide with customers drawings; **Material:** we could choose Nippon steel, Baosteel, WISCO and other steel plants products to meet customers core loss requirements; in order to make sure we choose the right material, we would like our customers to provide us with detailed drawings including necessary technical parameters.

Detailed ordering instructions below:

- 1, All sizes in the pictures?
- 2, Frequency (50Hz or 60Hz)?
- 3, Low voltage;
- 4, Turns (@ low voltage)
- 5, Max. No-load core losses?

Uni-Core for S13 100kVA Distribution Dry Type Transformer

Trade Capacity

International Commercial FOB, CIF, CFR

Terms(Incoterms): Terms of Payment: LC, T/T

Peak Season Lead Time: within 15 workdays, Off Season Lead Time: within 15 Average Lead Time:

workdays

Number of Foreign Trading

Staff:

Export Year: 2014-04-01

51%~70% Export Percentage:

Main Markets: North America, Southeast Asia/ Mideast, Others

Nearest Port: Shanghai

Import & Export Mode: Have Own Export License

Partner Production Capacity

Factory Address: Jingxin Rd 3-2#, Xibei Town, Wuxi, Jiangsu, China

OEM, ODM R&D Capacity: No. of R&D Staff: Less than 5 People

No. of Production Lines:

Annual Output Value: Below US\$1 Million

Company Show

Certificates

Record Regis

Record Registration Form for Foreign Trade Operators



Wuxi Jiachen Power Electronics Equipment Co., Ltd.





tangliang@jc-cores.com



jc-transformer.com

No. 68, Zhounan Road, Wanshi Town, Yixing City, Jiangsu Province, China